

Touch-Screen Master Station

ViLX-TMS3-W-8



All LexiComm Emergency Voice Communications Systems (EVCS) are designed to comply fully with the requirements of BS 5839-9:2021 for use as a fire telephone system (FT), disabled refuge system (DRS) or as a combined system when both fire telephones and disabled refuge call points are required.

- 4.3" Full colour touchscreen
- Fully compliant to BS 5839-9:2021
- Integrated Assist Call with acknowledge meeting BS8300
- Full duplex operation
- Alarm icon choice
- Expandable from 2 to 512 lines
- Dual redundant fault tolerant network
- Peer-to-peer network
- Pager serial output port

Overview

An EVCS is a fixed, secure, bi-directional, full duplex voice communication system. It can provide either disabled refuge system functions and provide a fire telephone system where required. The LexiComm Network system is suitable for small to medium installation but is particularly suited to large multistorey and campus sites due to its superior network capability.

System Architecture

The range consists of a touchscreen master station, touchscreen repeater and system expander panels. These panels are connected via a dedicated secure network of up to 64 panels. Each master station or expander panel can have eight radial lines wired from it, this gives a system capacity of 512 lines.

Touchscreen Interface

Control and indication functions utilise a 4.3" colour touchscreen, this intuitive user interface makes use of icons wherever possible, which simplifies the user experience. Extensive logging of all functions can be accessed via the screen, this information is stored on the micro SD card and can be analysed in a daily spreadsheet format.

Outstation Range

The full range of LexiComm outstations are compatible and include Type A outstations, Type B outstations, Type C

outstations and jack points for use in far and Middle East applications. Lines auto identify by flashing red for EVCS calls, blue for assist calls or flashing green for connected calls as detailed in BS 5839-9:2021.

Emergency Assistance Alarms

The Assist Call range of emergency assistance alarms is fully compatible. It has become very popular to add these devices as an integrated system. This has several benefits, namely: fault monitored wiring, fully line powered (no mains supply), battery back-up via the master station.

Alarm Icon Configuration

Icons used for alarm purposes can be altered for alternative uses, examples are: pool alarm, panic alarm, medicine cabinet alarm and fire door monitoring.

Pager Output

The TMS3 master station has the facility to connect to a Scope CX6 pager system via the optional adapter board. This provides text location text information for EVC outstations and Assist Call emergency assistance alarms.

Assist Call Repeater

The ViLX-ACR Assist Call Repeater can now be connected to the TMS3 master station directly via the Adapter board. This is ideal for reception areas providing notification of emergency assistance alarm activation. See relevant datasheet for full information.

Touch-Screen Master Station


VILX-TMS3-W-8

Larger Sites

The Lexicomm Network system is particularly well suited for larger projects as it can accommodate multiple master station positions where alternative points of control are required. The Lexicomm Network system can be easily extended by simply adding a system expander panel where the additional lines are required.

Configuration

The touchscreen display allows for extensive configuration menus. An engineer can configure VA and EVC functions from a single panel through to a multi-panel network all from one position without the need for a PC, all configuration being held on a micro SD card.



Technical Specification

Details	VILX-TMS3-W-8
Power Supply and Charger	
AC Input	120-240VAC+10%-15% 50/60Hz
Internal supply	5V, 16V, 27V DC
Supply and battery	Monitored Open, Short, Fuses, High Impedance
Protection	Deep discharge, Short, Thermals
Battery type	1x 12V 7AH VRSLA
Mains fuse	240V 1A HRC
Battery fuse	750mA PTC
Max charge current	500mA

Details		VILX-TMS3-W-8	
Inputs			
Lines		2-8 in 2 line blocks	
Remote enable		Short to use	
End of line		10kΩ	
Outstation Cables			
Type	Cores	Distance from Master Station	
Standard*/Enhanced	1× 2 core radial 1mm or 1.5mm	500m	
Outputs			
Number		2, Fault & In use	
Fault Relay		1× Volt free NC, Com 30V DC 1A	
In Use Relay		1× Volt free NO, Com 30V DC 1A	
Controls			
Navigation Buttons		3 push button navigation keys	
Fault indicators		AC, DC, PSU Status	
Statutory indicators		CPU fault indicator	
		General fault indicator	
		RGB mode indicator	
		AC DC Present	
Touchscreen		4.7” RGB touchscreen	
Network Cables			
Type	Cores	Distance max between panels	
Standard*/Enhanced	2× 2 core loops, 1mm or 1.5mm (2c Data, 2c Audio)	500m	
Standards Compliance			
EMC	EN 55035:2017+A11:2020 EN 55032:2015+A1:2020		
LVD	EN IEC62368-1:2020+A11:2020		
Product Family	BS 5839-9:2021, BS 9999:2017, BS 8300-2:2018		
Dimensions			
	Panel	Bezel	Cut-out
Height	300mm	350mm	305mm
Width	350mm	400mm	355mm
Depth	95mm	1mm	85mm
Weight	4.5kg		
Part Numbers			
Touch Screen Master Station		VILX-TMS3-W-8	

*Refer to BS 5839-9:2021 for exceptions

Touch-Screen Master Station

VILX-TMS3-W-8

